

FA6829S Ultra Slim Carbon Monoxide Alarm

Sensor type	Electrochemical
Battery type	10 year sealed for life lithium



- Ultra slim CO alarm with easy access front cover designed to work as a Test / Silence button.
- IP44 grade rating, provides protection against water splashes, ideal for a variety of environments.
- 10 year sealed for life lithium battery.
- Sleep Easy - allows a low battery chirp to be silenced for 9 hours, this function can be used up to 10 times.
- Optional anti-tamper feature to prevent unauthorised removal.
- Night mode feature - senses ambient light and reduces the brightness of the standby LED.
- End of Life Indication - a clear reminder to replace the alarm, which can be silenced.



KM694290
BS EN 50291-1:2018
BS EN 50291-2:2019

Technical Specification

Dimensions	95mm (width) x 95mm (height) x 25mm (depth)	
Supply voltage	3V DC	
Battery	10 year sealed for life lithium battery	
Sensor technology	Electrochemical	
Alarm sound level	85dB(A) at 3m (minimum)	
Installation positions	Wall / Free standing / Portable	
Operating temperature	-10°C to +40°C	
Operating humidity	25% to 95% RH (non condensing)	
Storage temperature	-20°C to +50°C	
Storage humidity	Up to 95% RH (non condensing)	
Warranty	5 Years	
Certified to	BS EN 50291-1:2018, BS EN 50291-2:2019	
Weight	120g	
Leisure Accomodation Vehicles	Yes	